ULC0521C18

1-Line Low Capacitance Bi-directional TVS Diode


Features

- typical Ultra low leakage: nA level
- Low operating voltage: 5 V
- Low clamping voltage
- 2-pin leadless package
- Complies with following standards:
  - – IEC 61000-4-2 (ESD) immunity test
    Air discharge: ±11kV
    Contact discharge: ±11kV
  - –IEC61000-4-5 (Lightning) 5A (8/20μs)
- RoHS Compliant

Dimensions DFN0603



Pin Configuration



Applications

- USB Ports
- SIM Ports
- Smart Phones
- Wireless Systems
- Set-top box and digital TV
- Digital video interface (DVI)
- Ethernet 10/100/1000 Base T

Mechanical Characteristics

- Package: DFN0603
- Lead Finish: Lead Free
- UL Flammability Classification Rating 94V-0
- Quantity Per Reel:10,000pcs
- Reel Size:7 inch
- Device Marking: 9S

Absolute Maximum Ratings(Tamb=25°C unless otherwise specified)


Parameter	Symbol	Value	Unit
Peak Pulse Power (8/20μs)	Ppp	40	W
ESD per IEC 61000−4−2 (Air)	V_{ESD}	± 11	kV
ESD per IEC 61000−4−2 (Contact)		± 11	
Operating Temperature Range	T_J	-40 to +125	℃
Storage Temperature Range	T_{STJ}	-55 to +150	℃

Electrical Characteristics(TA=25°C unless otherwise specified)


Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
Reverse Working Voltage	V_{RWM}				5. 0	V
Breakdown Voltage	V_{BR}	I_T = 1mA	6.5	10.5		V
Holding Voltage	V_h	I_T = 30mA	1.5	2.1		V
Reverse Leakage Current	I_R	V_{RWM} = 5. 0V			0.2	μA
Clamping Voltage	V_C	I_{PP} = 1A (8 x 20μs pulse)		3.0		V
Clamping Voltage	V_C	I_{PP} = 5A (8 x 20μs pulse)		5.5	8.0	V
ESD Dynamic Turn on Resistance	R_{DYN}	T_P = 10/100 ns		0.47		Ω
ESD Clamping Voltage	VCL-ESD	IEC 61000-4-2 +8kV (ITLP = 16A), Contact mode, T=25 °C.		9.9		V
Junction Capacitance	C_J	VR = 0V, f = 1MHz		0.17	0.25	pF

Electrical Parameters(TA=25°C unless otherwise specified)


Symbol	Parameter
I_T	Test Current
I_{PP}	Maximum Reverse Peak Pulse Current
Vc	Clamping Voltage @Ic




Typical Performance Characteristics(TA=25°C unless otherwise specified)




Junction Capacitance vs. Reverse Voltage




Clamping Voltage vs. Peak Pulse Current




8 X 20us Pulse Waveform



IEC61000−4−2 Pulse Waveform




Power Derating Curve




TLP Curve

DFN0603 Package Outline Drawing



SYM	DIMENSIONS		
	MILLIMETERS		
	MIN	NOM	MAX
A	0.230		0.330
A1	0.000	0.020	0.050
b	0.215	0.245	0.275
c	0.120	0.150	0.180
D	0.550	0.600	0.650
e	0.355 BSC		
E	0.250	0.300	0.350
L	0.160	0.190	0.220
h	0.079 BSC		

Suggested Land Pattern



SYM	DIMENSIONS	
	MILLIMETERS	INCHES
X	0.30	0.012
Y1	0.25	0.010
Y2	0.15	0.006
Y3	0.40	0.016
Z	0.65	0.026

NOTICE
Leiditech reserves the right to make modifications,enhancements,improvements,corrections or other changes without further notice to any product herein. Leiditech does not assume any liability arising out of the application or use of any product described herein.

Shanghai Leiditech Electronic Technology Co., Ltd.
Email: sale1@leiditech.com
Tel : +86- 021 50828806
Fax : +86- 021 50477059